

# PC Floor Guard



Protector for Glazy Concrete Floors

---

## Product Overview

PC Floor Guard is a water based floor protector and color guard which has been especially designed for protecting dyed/colored concrete floors. It prevents incursion of dust into the polished and densified concrete floors

## Areas of applications

For all kinds of polished concrete floors.

## Properties

1. PC Floor Guard is compliant to VOC norms.
2. It is water based and has less odour.
3. It increases the reflectiveness and sheen of the concrete floors without buffing.
4. It makes the floors easier to maintain
5. It highlights the color of the floor and protects from UV rays damage.

## Guidelines for Usage

PC Floor Guard is designed for application over densified /polished concrete surfaces.

- 1. Surface preparation:** The concrete floor must be clean free from dust, oil, grease and other laitance and contaminants.
- 2. Application:** Using a suitable pump sprayer spray PC Floor guard evenly and using a microfiber pad, spread it immediately. Then allow it to dry for 15-30 mins and again repeat the same. Floor buffing can be done if more sheen or shininess is desired.

Periodic maintenance operations can be performed to achieve best of floor's appearance and protective qualities

## Coverage area

The recommended application rate is 12-17 m<sup>2</sup>/ltr. depending upon the texture of the surface.

## Packages available

PC Floor Guard is available in 210 kg HDPE barrels and 25 kg carboys.

## Storage and Shelf life

PC Floor Guard has 12 months shelf life when stored in original, dry and unopened packs.

## Safety Measures

1. Clean tools and equipment immediately after the use.
2. Don't use PC Floor Guard on wood, metal or glass surfaces, because they may cause etching and decolorization and dull the finish.
3. Use proper safety equipments while mixing e.g. use of safety coats, safety goggle, gloves etc. Any eye contamination should be washed immediately with clean water and immediate medical attention sought.

For further information related to application and safety precautions, please contact Mcrete technical representative.

## Technical data

Aspect	Milky White Liquid
Density	1.01 - 1.02 g/cc
pH	Min. 12
Tack free	15-30 mins
% of solids	(9-11) %
VOCs	35 g/ltr.

For further clarifications Please contact on below address

### Pinjala Chemicals Pvt. Ltd.

Plot No. 172/A, Road No. 24, Phase 2  
Mallapur IDA, Hyderabad-500076,  
Email: [info@mcrete.com](mailto:info@mcrete.com), Website: [www.mcrete.com](http://www.mcrete.com)  
Ph no: +919985898569, 040-27158569

### Pinjala Chemicals Inc.

30273 Eastridge Drive, Spring,  
Texas 77386, USA  
Email: [info.us@mcrete.com](mailto:info.us@mcrete.com), Website: [www.mcrete.com](http://www.mcrete.com)  
Ph no: 001-3136861237